





LABORATORY BALANCES

Advanced Weighing Technologies



5Y SERIES



	Ultra-microbalances	Microbalances	Microbalances	Analytical balances
Technical specifications	UYA 5Y UYA 5Y.F for filters	MYA 5Y MYA 5Y.P for pipettes MYA 5Y.F for filters MYA 5Y.F1 for filters	XA 5Y.M.A XA 5Y.M* XA 5Y.M.A.P for pipettes XA 5Y.M.A.S for stents	XA 5Y.A XA 5Y* XA 5Y.F* for filters
Maximum capacity [Max]	2.1 – 6.1 g	0.8 – 52 g	6 g – 53 g	52 – 520 g
Readability [d]	0.1 µg	1 – 10 µg	1 – 5 µg	0.01 – 1 mg
Standard repeatability [5% Max]**	0.15 – 0.2 µg	0.8 – 1.2 µg	0.6 – 1.2 µg	0.005 – 0.07 mg
Stabilization time***	10 – 20 s	8 s	4 s	1.3 – 4 s, 30 s**
Adjustment	Internal	Internal	Internal	Internal
Levelling system	Automatic – Reflex Level System	Automatic – Reflex Level System	Automatic – Reflex Level System *Semi-automatic LevelSENSING	Automatic – Reflex Level System *Semi-automatic LevelSENSING
Display	10" colour touchscreen	10" colour touchscreen	10" colour touchscreen	10" colour touchscreen
Weighing pan dimensions	UYA 5Y – ø16 mm UYA 5Y.F – ø70 for filters + ø16 mm	MYA 5Y – ø26 mm MYA 5Y.P – ø26 mm MYA 5Y.F – ø70 for filters + ø16 mm MYA 5Y.F1 – ø160 for filters + ø16 mm	XA 5Y.M.A – ø30 mm XA 5Y.M – ø30 mm XA 5Y.M.A.P – ø26 mm XA 5Y.M.A.S – ø30 mm + intended for stents	XA 5Y.A – ø90, ø100, ø85 (option) mm XA 5Y – ø90, ø100, ø85 (option) mm XA 5Y.F – ø90, ø85 (option), 210×254 mm for filters
Communication interfaces	USB-A *2, USB-C, HDMI, Ethernet, Wi-Fi@****, Hotspot	USB-A *2, USB-C, HDMI, Ethernet, Wi-Fi@****, Hotspot	USB-A *2, USB-C, HDMI, Ethernet, Wi-Fi@****, Hotspot	USB-A *2, USB-C, HDMI, Ethernet, Wi-Fi@****, Hotspot



*semi-automatic LevelSENSING Levelling System **for filters ***for moisture analyzers, the given values of other parameters ****Wi-Fi® is a registered trademark of Wi-Fi Alliance®.

X7 SERIES






	Analytical balances	Precision balances	Precision balances	Moisture Analyzers
Technical specifications	AS X7	PS X7	WLC X7	MA X7
Maximum capacity [Max]	60 – 3100 g	200 – 10100 g	0.2 – 21 kg	50 – 210 g
Readability [d]	0.01 – 1 mg	1 – 10 mg	0.001 – 1 g	0.1 – 1 mg
Standard repeatability [5% Max]*	0.01 – 0.5 mg	0.5 – 5 mg	0.0014 – 0.8 g	Moisture content readability 0.001 %
Stabilization time*	2 – 3 s	1.5 – 3 s	2 – 3 s	Drying temp. range max 160°C, 250°C
Adjustment	Internal	Internal	Internal (up to 6 kg), External	External
Levelling system	Semi-automatic LevelSENSING	Manual	Manual	Manual
Display	7" colour touchscreen	7" colour touchscreen	7" colour touchscreen	7" colour touchscreen
Weighing pan dimensions	ø90, ø100, ø85 (option) mm	128×128, 195×195	195×195, ø100 mm	ø90 mm, h = 8 mm
Communication interfaces	RS232, USB-A *2, USB-B, Ethernet, Wi-Fi@**	RS232 *2, USB-A, USB-B, Ethernet, Wi-Fi@**	RS232 *2, USB-A, USB-B, Ethernet, Wi-Fi@**	RS232, USB-A, USB-B, Ethernet, Wi-Fi@**

*for moisture analyzers, the given values of other parameters **Wi-Fi® is a registered trademark of Wi-Fi Alliance®.



Analytical balances	Precision balances	Precision balances	Moisture Analyzers	Moisture Analyzers
AS 5Y	PS 5Y	5Y.PM	PMV 5Y microwave	MA 5Y
60 – 3100 g	200 – 10100 g	10 – 120 kg	50 g	50 – 210 g
0.01 – 1 mg	1 mg – 10 mg	0.01 – 0.2 g	0.1 mg	0.1 – 1 mg
0.01 – 0.5 mg	0.5 – 5 mg	0.004 – 0.082 µg	Moisture content readability 0.0001 %	Moisture content readability 0.001 %
2 – 3 s	1.5 – 3 s	1 s	Heating power 800 W	Drying temp. range max 160 °C, 250 °C
Internal	Internal	Internal	External	Internal
Semi-automatic LevelSENSING	Semi-automatic LevelSENSING	Semi-automatic LevelSENSING	Semi-automatic LevelSENSING	Semi-automatic LevelSENSING
10" colour touchscreen	10" colour touchscreen	10" colour touchscreen	10" colour touchscreen	10" colour touchscreen
ø90, ø100, ø85 (option) mm	128×128, 195×195 mm	200×185, 350×260 mm	Intended for glass fibre filter ø 90 mm	ø90 mm, h = 8 mm
USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi®****, Hotspot	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi®****, Hotspot	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi®****, Hotspot	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi®****, Hotspot	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi®****, Hotspot



X2 SERIES



	Analytical balances	Precision balances ^a	Precision balances ^a	Moisture Analyzers
Technical specifications	AS X2	PS X2	WLC X2	MA X2
Maximum capacity [Max]	60 – 3100 g	200 – 10100 g	0.2 – 21 kg	50 – 210 g
Readability [d]	0.01 – 1 mg	1 – 10 mg	0.001 – 1 g	0.1 – 1 mg
Standard repeatability [5% Max]*	0.01 – 0.5 mg	0.5 – 5 mg	0.0014 – 0.8 g	Moisture content readability 0.001 %
Stabilization time*	2 – 3 s	1.5 – 3 s	2 – 3 s	Drying temp. range max 160°C, 250°C
Adjustment	Internal	Internal	Internal, External	External
Levelling system	Semi-automatic LevelSENSING	Manual	Manual	Manual
Display	5" colour touchscreen	5" colour touchscreen	5" colour touchscreen	5" colour touchscreen
Weighing pan dimensions	ø90, ø100, ø85 (option) mm	128×128, 195×195	195×195, ø100 mm	ø90 mm, h = 8 mm
Communication interfaces	RS232, USB-A ×2, USB-B, Ethernet, Wi-Fi®**	RS232 ×2, USB-A, USB-B, Ethernet, Wi-Fi®**	RS232 ×2, USB-A, USB-B, Ethernet, Wi-Fi®**	RS232, USB-A, USB-B, Ethernet, Wi-Fi®**

*for moisture analyzers, the given values of other parameters **Wi-Fi® is a registered trademark of Wi-Fi Alliance®.

R SERIES



	Analytical balances	Precision balances	Precision balances	Moisture Analyzers
Technical specifications	AS R1 PLUS AS R2 PLUS	PS R1 PS R2	PS R2.H hermetic interfaces	MA R
Maximum capacity [Max]	60 – 3100 g	200 – 10100 g	200 – 6100 g	50 – 210 g
Readability [d]	0.01 – 1 mg	1 mg – 10 mg	1 mg – 10 mg	0.1 – 1 mg
Standard repeatability [5% Max]*	0.012 – 0.08 mg	0.5 – 5 mg	0.5 – 5 mg	Moisture content readability 0.001 %
Stabilization time*	2 – 2.5 s	1.5 – 2 s	1.5 – 2 s	Drying temp. range max 160°C, 250°C
Adjustment	R2 – Internal, R1 - External	R2 – Internal, R1 - External	Internal	Internal
Levelling system	Manual	Manual	Manual	Manual
Display	LCD (backlit)	LCD (backlit)	LCD (backlit)	LCD (backlit)
Weighing pan dimensions	ø90, ø100, ø85 (option) mm	128×128, 195×195 mm	ø100 mm	ø90 mm, h = 8 mm
Communication interfaces	RS232 ×2, USB-A, USB-B, Wi-Fi®**	RS232 ×2, USB-A, USB-B, Wi-Fi®**	Hermetic: RS232, USB-A, USB-B, Wi-Fi®**	RS232, USB-A, USB-B, Wi-Fi®**

*for moisture analyzers, the given values of other parameters **Wi-Fi® is a registered trademark of Wi-Fi Alliance®.

OTHER LABORATORY BALANCES



	Precision balances	Precision balances	Precision balances	Precision balances
Technical specifications	CY10	C32.PM	WLY	WLC C/2 WLC WTC
Maximum capacity [Max]	1 – 120 kg	10 – 120 kg	1 – 120 kg	0.2 – 10 kg
Readability [d]	0.01 g – 2 g	0.01 – 0.2 g	0.01 – 2 g	0.001 – 1 g
Standard repeatability [5% Max]	0.03 – 2 g	0.41 – 0.082 g	0.03 – 2 g	0.002 – 1 g
Stabilization time	3 s	1 s	3 s	2 s
Adjustment	External	Internal	External	External
Levelling system	Manual	Manual	Manual	Manual
Display	10" colour touchscreen	5" colour	5.7" colour touchscreen	LCD (backlit)
Weighing pan dimensions	195×195, 300×300, 400×500 mm	200×185, 350×260 mm	195×195, 300×300, 400×500 mm	128×128, 195×195, 300×300, 400×500 ø100 mm
Communication interfaces	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi®*, Hotspot	2×RS232, USB-A, USB-B, Ethernet, Wi-Fi®*	2×RS232, 2×USB-A, Ethernet, 4IN/4OUT (digital), Wi-Fi®*	2×RS232, USB-A, USB-B, 4IN/4OUT

*Wi-Fi® is a registered trademark of Wi-Fi Alliance®.